

**MODEL: CPD10A
CPD10B**





The stand up design allows clear view of the handling process and quick entry and exit in tight area.



Highly maneuverable lift trucks can move goods with precision in tight area.



- Turning radius 1140mm, lower noise, no pollution
- Electromagnetic brake mechanism and drive power motor braking improves overall efficiency and prolongs brake component life.
- Advanced control system with MOSFET delivers smooth driving speed control for precise positioning of the truck.
- Hydrostatic power steering provides quiet, effortless and responsive operation for precise manoeuvrability.



| Model | | CPD10A | CPD10B |
|--|---------|------------------|-------------------|
| Power unit | | Battery | Battery |
| Load capacity | Q (t) | 1.0 | 1.0 |
| Load centre | C (mm) | 800 | 500 |
| Axle centre to fork face | A4 (mm) | 140 | 190 |
| Wheelbase | A3 (mm) | 975 | 1050 |
| Service weight | kg | 2050 | 2150 |
| Mast stage | | Duplex lift mast | Triplex lift mast |
| Free lift | H1 (mm) | 1600 | — |
| Max. Lift Height | H2 (mm) | 3000 | 5000 |
| Height of mast, lowered | H3 (mm) | 2155 | 2250 |
| Height of mast, extended | H4 (mm) | 3565 | 5600 |
| Minimum clearance from ground | H5 (mm) | 50 | 50 |
| Height of overhead guard (cablin) | H6 (mm) | 2090 | 2090 |
| Overall length | A1 (mm) | 2210 | 2250 |
| Overall width | B1 (mm) | 850 | 850 |
| Aisle width with pallet 100 × 1200 crosswise | W (mm) | 2600 | 2900 |
| Aisle width with pallet 80 × 1200 lengthwise | W (mm) | 2750 | 2750 |
| Turning radius | R (mm) | 1140 | 1180 |
| Travel speed, with/without load | km/h | 5.8/6.0 | 5.8/6.0 |
| Lifting speed, with/without load | m/s | 0.11/0.15 | 0.11/0.15 |
| Lowering speed, with/without load | m/s | 0.15/0.11 | 0.15/0.11 |
| Maximum climbing ability, with/without load | % | 8/12 | 8/12 |
| Tyre size, front | (mm) | 250 | 250 |
| Tyre size, rear | (mm) | 280 | 280 |
| Drive motor | kw | 1.5 | 1.5 |
| Lift motor | kw | 3.0 | 3.0 |
| Battery voltage/rated capacity | V/Ah | 24/360 | 24/360 |

- Turning radius 1140mm, lower noise, no pollution
- Electromagnetic brake mechanism and Drive power motor Braking improves overall efficiency and prolongs brake component life.
- Advanced Control System with MOSFET delivers smooth driving speed control for precise positioning of the truck.
- Hydrostatic Power Steering provides quiet, effortless and responsive operation for precise manoeuvrability.

| Model | | CPD10A | CPD10B |
|---|---------|------------------|-------------------|
| Power unit | | Battery | Battery |
| Load capacity | Q (t) | 1.0 | 1.0 |
| Load centre | C (mm) | 600 | 500 |
| Axle centre to fork face | A4 (mm) | 140 | 180 |
| Wheelbase | A3 (mm) | 975 | 1050 |
| Service weight | kg | 2050 | 2150 |
| Mast stage | | Duplex lift mast | Triplex lift mast |
| Free lift | H1 (mm) | 1600 | — |
| Max, Lift Height | H2 (mm) | 3000 | 5000 |
| Height of mast, lowered | H3 (mm) | 2155 | 2250 |
| Height of mast, extended | H4 (mm) | 3565 | 5600 |
| Minimum clearance from ground | H5 (mm) | 50 | 50 |
| Height of overhead guard (cabin) | H6 (mm) | 2090 | 2090 |
| Overall length | A1 (mm) | 2210 | 2250 |
| Overall width | B1 (mm) | 850 | 850 |
| Aisle width with pallet 100×1200 crosswise | W (mm) | 2600 | 2600 |
| Aisle width with pallet 80×1200 lengthwise | W (mm) | 2750 | 2750 |
| Turning radius | R (mm) | 1140 | 1180 |
| Travel speed, with/without load | km/h | 5.8/6.0 | 5.8/6.0 |
| Lifting speed, with/without load | m/s | 0.11/0.15 | 0.11/0.15 |
| Lowering speed, with/without load | m/s | 0.15/0.11 | 0.15/0.11 |
| Maximum climbing ability, with/without load | % | 8/12 | 8/12 |
| Tyre size, front | (mm) | 250 | 250 |
| Tyre size, rear | (mm) | 230 | 230 |
| Drive motor | kw | 1.5 | 1.5 |
| Lift motor | kw | 3.0 | 3.0 |
| Battery voltage/rated capacity | V/Ah | 24/360 | 24/360 |

